

# S30



MULTISCAN TECHNOLOGIES S.L.

Pol Ind, Els Algars, Calle La Safor 2, 03820 Cocentaina (Alicante) Spain

Tno: 34 96 533 18 31 Fax: 34 96 533 26 30

info@multiscan.eu

www.multiscan.eu

# S 30 - Up to 6000 kg/h

**Selection of elaborated olives by quality, based on colour, intensity, shape, defects and fruit size.**

## Main features:

- Built in stainless steel and polymeric materials adequate for working with food
- Transport over roller belt
- Vision with a high-resolution digital camera
- Long life LED strobe lights
- Electronics in a sealed air-conditioned box
- Controlled by a sole PC working with Windows
- Pneumatic expulsion system with **three exits**
- Adequate for all kind of olives with sizes between 160 and 400 fruits/kilo
- Possibility of remote connexion with the Communications Option
- Software designed to provide a simple and versatile use through a touch screen.
- **Capacity: up to 6000 kg/h with the option of self-regulation.**

## Serial and optional equipment:

	EQUIPMENT						
	Three exits	Analysis of defects	Limitation of ejection	Auto-Adjustment of Production	Communications option	Tele - Maintenance	Revisions and Software update
S30	●	●	●	●	●	●	●

● SERIAL EQUIPEMENT

● OPTIONAL EQUIPEMENT OR SERVICE

\* Some options may not be available, depending on the country of destination.

## Technical features:

- Operating voltage: 230 Vac.  $\pm$  10% PH, 50/60Hz
- Power: 4.5 Kw
- Air supply: 1000 l / min for a 60% load and 30% of expulsion
- Operating Temperature / storage: 10 ~ 45 ° C / 5 ~ 50 ° C
- Operating Relative Humidity / storage: 80% non-condensing
- Pneumatic Pressure connection: 8 bar
- Pneumatic Pressure required for use: 6 bar
- Weight (kg): 800 kg